

Compact Scrubber Drier

Compact Scrubber Drier is the perfect machine for cleaning hard floor surfaces ranging from the roughest to the most delicate. Its versatility along with the low-profile base and the sleek upright body make it effortless to use with sparkling results. The floor remains perfectly dry allowing you to use the cleaned area immediately. The cleaning components, squeegees and roller can be easily removed without any tools for a quick rinse after using the machine.

Advanced, innovative, multifunction floor scrubber driers Cleans and dries in record time!

STRENGTHS

- Lightweight (under 25.1 pounds)
- The lightest weight for the operator (2.8 lbs.)
- The world lowest profile (5.5 in)
- Injection / extraction
- Minimum consumption of water and detergents

BGUS1500B L-ion

- Light, only (25.1 Lbs.)
- Replaceable lithium-ion battery (36V - 6Ah)
- Autonomy 25 min. - Charging time 90 min.
- Great flexibility and practicality

**Cleans and dries
in record time!**



LOW PROFILE
The base height is only 5.5 in. and allows easy access under low objects.

| TECHNICAL DATA | BGUS1500 | BGUS1500B |
|-----------------------------------|-------------------|--------------------------|
| Input power (W) | 900 | 550 |
| Water lift mm/H2O (in/H2O) | 1800 (70.9) | 1100 (39.4) |
| Air volume lt/sec (CFM) | 43 (89.3) | 26 (54) |
| Brush motor (W) | 250 | 150 |
| Brush roller constant speed (rpm) | 1500 | 1500 |
| Electronic overload control | Standard | Standard |
| Cylindrical brush D/L mm (in) | 72/335 (2.8/13.2) | 72/335 (2.8/13.2) |
| Suction width mm (in) | 358 (14) | 280 (11) |
| Solution Tank (lt.) | 2.6 | 2.6 |
| Recovery tank (lt.) | 2.6 | 2.6 |
| Working capacity m2/h (sq.ft/h) | 320 (3400) | 300 (3200) |
| Water dosing | Pump | Solenoid Valve |
| Working time per tank (min) | 9 | 15 |
| Base height mm (in) | 140 (5.5) | 140 (5.5) |
| Total weight Kg (lb) | 10.6 (23.3) | 11.4 (25.1) with battery |
| Handle weight Kg (lb) | 1.3 (2.8) | 1.9 (4.2) |
| Cord length mt. (ft) | 10 (41) | NA |
| Noise level db (A) | 70 | 69 |
| Sealing protection | IPX 4 | IPX 4 |